

Features

- Compact size with stand and mounting flexibility
- Excellent microprocessor control guarantees high reliability
- Auto restart while AC is recovering
- Simulated sine wave
- Cold start function



MODEL	NANO 400	NANO 600	NANO 800
CAPACITY	400 VA / 240 W	600 VA / 360 W	800 VA / 480 W
INPUT			
Voltage	220/230/240 VAC		
Voltage Range	180-270 VAC		
Frequency Range	50 Hz (auto sensing)		
OUTPUT			
AC Voltage Regulation (Batt. Mode)	±10%		
Frequency Range (Batt. Mode)	50 Hz ±1 Hz		
Transfer Time	Typical 2-6 ms		
Waveform (Batt. Mode)	Simulated Sine Wave		
BATTERY			
Battery Type & Number	12 V/4.5 Ah x 1	12 V/7 Ah x 1	12 V/9 Ah x 1
Typical Recharge Time	8 hours up to 90% capacity		
INDICATORS			
AC Mode	Green lighting		
Battery Mode	Green flashing		
ALARM			
Battery Mode	Sounding every 10 seconds		
Low Battery	Sounding every second		
Fault	Continuously sounding		
PROTECTION			
Full Protection	Overload, discharge, and overcharge protection		
PHYSICAL			
Dimension, D X W X H (mm)	228 x 82.5 x 207 (Vertically stand)		
Net Weight (kgs)	2.2	2.7	3.1
ENVIRONMENT			
Humidity	0-90 % RH @ 0- 40°C (non-condensing)		
Noise Level	Less than 40dB		

* Product specifications are subject to change without further notice